

## DuraSOL Light 220

— satin 3408 - 220 µm

Satin finish coated rigid PVC film. A waterfast and extremely tear resistant product. It is superbly suited for use in various display and roll-up systems.

### Applications

- Indoor signs
- Indoor adverts
- Pop-up / Roll-up Displays
- Outdoor signage

### Advantages

- High rigidity
- Waterfast prints
- High image definition
- Good flatness and low memory effect
- High scratch resistance

## DuraSOL Light 220

— satin 3408 - 220 µm

### List of Printers

Printer	Ink	Quality
Epson Stylus Pro GS6000 UltraChrome GS	Inkjet with Eco Solvent	Excellent
Roland VS 540 / VS 640	Inkjet with Eco Solvent	Excellent
Roland SolJET PRO4 XR-640	Inkjet with Solvent Ink	Excellent
Mimaki JV 33 / JV34 - 260	Inkjet with Eco Solvent	Excellent
Mimaki JV400SUV Serie	Inkjet mit Solvent-UV	Excellent
Mutoh ValueJet 1204 / 1304 /1614	Inkjet with Eco Solvent	Excellent
Océ CS9360 / CS935	Inkjet with Eco Solvent	Excellent
Hewlett Packard DJ 8000S / 9000S / 10000S	Inkjet with Eco Solvent	Good
ColorSpan DisplayMaker 72S	Inkjet with Eco Solvent	Good
Epson SureColor SC-30600 / 50600 / 70600	Inkjet with Eco Solvent	Good
Roland SolJet SJ540 / SC540 SJ 740 / SC740	Inkjet with Eco Solvent	Good
Roland SC-500 Permasol S	Inkjet with Solvent Ink	Good
Mimaki JV-3 160S, 250	Inkjet with Solvent Ink	Good
Mimaki JV 5-130 / -160 / -260 /-320	Inkjet with Eco Solvent	Good
Mimaki CJV 30	Inkjet with Eco Solvent	Good
Mimaki CV300 Series Eco Solvent	Inkjet with Eco Solvent	Good
Mutoh Rockhopper II 50", 64", 87"	Inkjet with Eco Solvent	Good
Mutoh Valuejet 1204 / 1304 / 1324 / 1614 / 1624 / 1638	Inkjet with Eco Solvent	Good
Océ CS6060	Inkjet with Eco Solvent	Good
Seiko SII Colorpainter 64S / 100S / W-54s/W-64s / H2-74s/H2-104s	Inkjet with Eco Solvent	Good
Mutoh Rockhopper 46", 62"	Inkjet with Eco Solvent	Fair

Last update: 05.11.2014

## DuraSOL Light 220

— satin 3408 - 220 µm

### Physical Properties

Weight (Total) [gsm]	310	ISO 536
Thickness (total) [microns]	220	ISO 534

### Conditions of Use

To sustain quality of this media, it should be stored and converted under the following conditions: 35 - 65 % humidity with temperatures of 10 - 30°C.

Keep the product in original packaging (cardboard box and PE bag). Cotton gloves should always be worn when handling inkjet media to avoid fingerprints.

The coating allows instant dry even with the low heating temperatures on eco- or true-solvent printers. The heaters should be set at maximum of 30°C to avoid waves.

[MediaSafetyDataSheet \(pdf\)](#)

The values provided on this datasheet are only for orientation.

Before using our media please check its compatibility for your printer and intended application. Technical specifications are subject to change, therefore we do not take responsibility for any misprints resulting from technically modified inks and/or printers.